

D12600D


DATA SHEET



Cyclic AGM Battery Block

Discover® AGM Series VRLA Industrial Batteries provide superior high integrity and reliability for commercial, industrial, and private applications. The maintenance-free Valve Regulated Lead Acid (VRLA) construction make Discover® Standard AGM Series Batteries the definitive choice for mobility and Home Medical Equipment (HME), solar and renewable energy, electronics and security, marine and RV, and utility applications.

Mechanical Drawings



Benefits and Features

- Tank formed lead-tin-calcium plates deliver consistent dependable performance and promote long life
- Maintenance-free technology
- 99% gas recombination for extended life in float applications
- Multiple terminal, configuration options and carrying handles available with most models
- Classified as a non-spillable battery and is not restricted for transportation by:
 - Air (IATA/ICAO provision 67)
 - Surface (DOT-CFR-HMR49)
 - Water (per IMDG amendment 27)
- Flame retardant ABS case and cover with UL94 V0 rating available
- UL924 recognized flame arresting low pressure safety vents
- 98% recyclable

Mechanical Specifications

| | | |
|------------------|----------|-----------|
| Length (A) | 9.01 in | 229 mm |
| Width (B) | 5.43 in | 138 mm |
| Height (C) | 8.19 in | 208 mm |
| Total Height (D) | 8.94 in | 227 mm |
| Weight | 36.3 lbs | 16.50 kgs |
| Terminal (Opt'l) | F5 (F11) | |
| Cells | 6 | |
| Electrolyte | AGM | |

TERMINAL TORQUE: Please refer to our document, located in the Resources webpage (www.discover-energy.com/resources/).

CAUTION: Extra considerations must be given to depths of discharge, operating voltages and currents when designing systems for use at maximum temperatures.

Electrical Specifications

| | |
|---------------------------|-------------------------------|
| Voltage | 12 V |
| Internal Resistance | 8mΩ |
| Short Circuit 20°C (68°F) | - |
| 20 HR | 60 Ah |
| 10 HR | 58 Ah |
| 5 HR | 48 Ah |
| 1 HR | 35 Ah |
| 15 MIN | - |
| Charge Temperature | -10°C (14°F) to 50°C (122°F) |
| Discharge Temperature | -20°C (-4°F) to 50°C (122°F) |
| Maximum Discharge* | -40°C (-40°F) to 60°C (140°F) |

Certifications and Standards

Designed in accordance with and published in compliance with applicable BCI, IEC and BS EN standards, including:

- IEC60896-21/22
- BS EN 60254-1:2005
- AS/NZS 4029.2:2000 BS EN 60254-1:2005 (MOD)

Discover® and its facilities and products are certified to multiple standards:

- ISO, UL, QS, and TUV standards
- EITS Germany
- Euro Bat classification for Environmental Stewardship Standards



Discharge Constant Current (Amperes at 25°C/77°F)

| End Point V/C | 5 MIN | 10 MIN | 15 MIN | 30 MIN | 1 HR | 3 HR | 5 HR | 10 HR | 20 HR |
|---------------|-------|--------|--------|--------|------|------|------|-------|-------|
| 1.60V | 172 | 130 | 98.0 | 58.2 | 35.0 | 14.5 | 9.98 | 5.99 | 3.08 |
| 1.65V | 162 | 123 | 94.0 | 56.5 | 34.2 | 14.3 | 9.88 | 5.95 | 3.07 |
| 1.70V | 152 | 115 | 89.5 | 54.5 | 33.4 | 14.0 | 9.75 | 5.90 | 3.05 |
| 1.75V | 141 | 108 | 84.4 | 52.9 | 32.5 | 13.7 | 9.60 | 5.85 | 3.03 |
| 1.80V | 128 | 100 | 50.5 | 51.0 | 31.4 | 13.4 | 9.43 | 5.80 | 3.00 |

Discharge Constant Power (Watts at 25°C/ 77°F)

| End Point V/C | 5 MIN | 10 MIN | 15 MIN | 30 MIN | 45 MIN | 1 HR | 2 HR | 3 HR | 5 HR |
|---------------|-------|--------|--------|--------|--------|------|------|------|------|
| 1.60V | 330 | 247 | 191 | 115 | 88.4 | 71.4 | 42.5 | 30.1 | 19.4 |
| 1.65V | 310 | 233 | 183 | 113 | 87.1 | 69.8 | 41.7 | 29.5 | 19.3 |
| 1.70V | 291 | 220 | 176 | 111 | 85.3 | 68.2 | 40.8 | 28.9 | 18.8 |
| 1.75V | 271 | 207 | 168 | 109 | 83.4 | 66.6 | 39.8 | 28.3 | 18.7 |
| 1.80V | 257 | 192 | 159 | 107 | 81.2 | 64.9 | 38.8 | 27.7 | 18.5 |

Contact Us



Unit 5-13511 Crestwood Place,
Richmond, BC, V6V 2E9, Canada
Email: info@discover-energy.com
www.discover-energy.com

Charge and Discharge

| Max Charge / Discharge Currents | Peak (5 seconds) | Peak (10 seconds) | Max Continuous |
|---------------------------------|------------------|-------------------|----------------|
| Charge | 1c20 | 0.75c20 | 0.25c20 |
| Discharge | 15c20 | 10c20 | 0.5c20 |

Float (Stand-By) Use: Hold a constant voltage of 2.25vpc to 2.30vpc continuously.

When held at this voltage, the battery will seek its own current level and maintain itself in a fully charged condition.

Cyclic Use: Limit initial currents to 0.25C20 amps. Charge until battery voltage reaches 2.40 to 2.45vpc. Hold at 2.40 to 2.45vpc until current drops to under 0.01C20 amps. Battery is fully charged under these conditions, and charger should be disconnected or switched to "float" voltage.

Temperature Coefficient: Adjust charging voltage to +/- 0.005vpc (C, 0.003vpc/F) from 25°C (77°F).


Discharge Characteristics (20°C/68°F)




Self-Discharge Characteristics




Life Characteristics in Stand-By Use



Life Characteristics in Cyclic Use



Temperature Effects on Capacity



Temperature Effects on Float Life

