

Product Range

Type No.	NOMINAL CAPACITY					Kilo-Watt Hours (120 HRS)	Poles	MECHANICAL CHARACTERISTICS							
	240 HR	120 HR	100 HR	20 HR	10 HR			Length		Width		Height*		Weight	
	1.85VPC at 20°C / 68°F			1.75VPC at 27°C / 80°F				IN	MM	IN	MM	IN	MM	LB	KG
2 VOLT CELLS															
2VRE-600TG	307	305	301	246	224	0.61	2	4.1	103	8.1	206	15.0	382	44	20
2VRE-800TG	382	380	376	308	280	0.76	2	4.9	124	8.1	206	15.0	382	53	24
2VRE-900TG	459	457	452	370	336	0.91	2	5.7	145	8.1	206	15.0	382	62	28
2VRE-1100TG	567	564	556	446	405	1.13	2	4.9	124	8.1	206	19.6	498	68	31
2VRE-1300TG	681	678	668	535	486	1.36	2	5.7	145	8.1	206	19.6	498	82	37
2VRE-1600TG	797	793	782	624	567	1.59	2	6.5	166	8.1	206	19.6	498	93	42
2VRE-1900TG	987	982	968	759	690	1.96	2	5.7	145	8.1	206	26.5	673	110	50
2VRE-2600TG	1313	1306	1287	1012	920	2.61	4	7.5	191	8.3	210	26.5	673	150	68
2VRE-3200TG	1643	1635	1610	1265	1150	3.27	4	9.2	233	8.3	210	26.5	673	181	82
2VRE-3900TG	1979	1969	1938	1518	1380	3.94	4	10.8	275	8.3	210	26.5	673	214	97
2VRE-4400TG	2238	2227	2197	1782	1620	4.45	4	10.8	275	8.3	210	32.4	824	265	120
2VRE-5900TG	2981	2966	2927	2376	2160	5.93	6	15.7	399	8.4	214	31.5	799	364	165
2VRE-7400TG	3723	3704	3655	2970	2700	7.41	8	19.2	487	8.3	212	31.5	799	441	200
2VRE-8900TG	4483	4461	4402	3564	3240	8.92	8	22.7	576	8.3	212	31.5	799	529	240
6 & 12 VOLT BLOCKS															
6VRE-1600TG	268	267	264	227	206	1.60	2	10.7	272	8.1	205	14.6	371	106	48
6VRE-2000TG	337	335	331	283	257	2.01	2	15.0	380	8.1	205	14.6	371	139	63
6VRE-2400TG	404	402	398	340	309	2.41	2	15.0	380	8.1	205	14.6	371	154	70
12VRE-800TG	67	66	65	56	51	0.79	2	10.7	272	8.1	205	14.6	371	95	43
12VRE-1600TG	133	132	131	112	102	1.58	2	10.7	272	8.1	205	14.6	371	115	52
12VRE-2400TG	200	199	197	168	153	2.39	2	15.0	380	8.1	205	14.6	371	159	72

*Includes installed connectors and shrouds.

Drawings

